



SECTION A-A

MAX STROKE: 30 mm

MINIMUM BENDING RADIUS: 200 mm

TEST LOAD OF WIRE ROPE / CONDUIT TERMINAL: 1470 N

DISCONNECTION LOAD OF WIRE ROPE / CONDUIT TERMINAL: 3550 N

CABLE DRAWING AT REST

GENERAL LINEAR TOLERANCES: UNTIL 100 ±0,15 OVER ±0,15 %

GENERAL ANGULAR TOLERANCES: ±0,5°

CODE	DESCRIPTION	TOTAL LENGTH (mm)
IB-741616/01.60	CAVO	1600
IB-741616/01.80	CAVO	1800
IB-741616/02.00	CAVO	2000
IB-741616/02.20	CAVO	2200
IB-741616/02.40	CAVO	2400
IB-741616/02.60	CAVO	2600

MODIFICA (mod)	DATA (date)	FIRMA UFF. TECHN. (technical sign)	DESCRIZIONE DELLA MODIFICA (mod description)

	DISEGNATO DA (drawn by): FIRMA (sign): CONTROLLATO DA (checked by):	CATEGORIA MERCATOLOGICA (commodity sector): IB	DESCRIZIONE (description): CABLE	NUMERO DI DISEGNO (drawing number): 741616
	FORMATO FOGLIO (sheet size): A3	CODICE CLIENTE (customer code):	SCALA: 1:1 (scale)	PROIEZIONE EUROPEA (european projection)